

Two Stage Gasoline

30-Gallon

The 30-gallon storage tank gives you air capacity for extra productivity, you'll have the electrical power to operate air tools in your shop or in the most remote locations.



AG2-SR14-30M

Powered by



Compressor Pump

- ✓ Splash lubricated cast iron crankcase
- ✓ Stainless-steel braided discharge hose
- ✓ Large canister intake filter

Generator

- ✓ Brushless alternator
- ✓ Total harmonic distortion (THD) less than 6%
- ✓ 100% copper windings
- ✓ Comes standard with (2) NEMA 5-15R and (1) NEMA L6-20R receptacles

Frame


- ✓ Powder coated ASME coded 30-gallon receiver tank
- ✓ 3/16-inch base plate to reduce vibration
- ✓ 14-gauge powder coated two-piece belt guard

Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ 16.5-inch fly wheel
- ✓ Manual drain valves for proper maintenance
- ✓ Quality pilot valve unloader

Limited Warranties:

- | | |
|--------------------------------|--------------------------------|
| 1 Year
Mi-T-M Engine | 3 Year
Honda Engine |
| 2 Year
Pump Exchange | 3 Year
Kohler Engine |
| 2 Year
Alternator | 5 Year
Subaru Engine |



To see more online, scan here or go to www.mitm.com:



Performance Under Pressure.®

Two Stage Gasoline

30-Gallon



AG2-SH13-30M
POWERED by
HONDA

MODEL NUMBER	CFM @ 90 PSI	CFM @ 175 PSI*	MAX. OUTPUT	ALTERNATOR WATTAGE		RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
				CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD							
AG2-SH13-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-15R, (1) NEMA L6-20R	389cc Honda OHV	Two stage	Cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SK14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-15R, (1) NEMA L6-20R	429cc Kohler OHV	Two stage	Cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SM14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-15R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage	Cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SR14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-15R, (1) NEMA L6-20R	404cc Subaru OHC	Two stage	Cast iron	40x24.5x45in.	550 lb.	450 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
70-0358	Engine oil drain	AG2-SH13-30M, AG2-SK14-30M & AG2-SM14-30M	AX-0065	Electric start (battery box and cables included, battery not included)	AG2-SR14-30M
70-0380	Engine oil drain	AG2-SR14-30M	AX-0068	Idle down (includes electric start)	AG2-SH13-30M
854-0093	Service truck mount kit (recommended for models that are mounted in service truck applications)	All models	AX-0069	Idle down (includes electric start)	AG2-SR14-30M
AW-6000-1002	Equipment cover	All models	AX-0071	Electric start (battery, box and cables not included)	AG2-SK14-30M
AX-0019	Electric start (battery, box and cables not included)	AG2-SH13-30M	AX-0072	Electric start (battery box and cables included, battery not included)	AG2-SK14-30M
AX-0062	Electric start (battery, box and cables not included)	AG2-SR14-30M	AX-0073	Electric start (battery, box and cables not included)	AG2-SM14-30M
AX-0063	Lifting hook	All models	AX-0074	Electric start (battery box and cables included, battery not included)	AG2-SM14-30M
AX-0064	Electric start (battery box and cables included, battery not included)	AG2-SH13-30M	IX-0001	Vibration pads	All models