

Single Stage Electric

The 20-gallon electric air compressor provides extra air storage that allows you to operate multiple tools at the same time and is the perfect solution for busy contractor jobsites.

To see more online, scan here
or go to www.mitm.com:



Compressor Pump

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Motor

- Auto start/stop - continuous run optional
- Thermal overload motor protection

Frame

- Powder coated ASME coded 20-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Flat-free tires

Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 10-inch fly wheel
- Industrial-grade pressure switch



AM1-PE15-20M

Limited Warranties:

1 Year
Electric Motor



2 Year
Pump Exchange

See page 60 for information

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	TANK SIZE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PE15-20M	7.3 @ 90	1.5 HP, 120V, 13.2A	Single stage, cast iron	20-gallon	NEMA 5-15P	40x24x32in.	265 lb.	196 lb.
AM1-PE02-20M	9.2 @ 90	2.0 HP, 120V, 18.8A	Single stage, cast iron	20-gallon	NEMA 5-20P	40x24x32in.	272 lb.	203 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	All models	AX-0003	Manual drain/regulator/metal bowl	All models
AX-0002	Auto drain/regulator/plastic bowl	All models	AX-0008	Dual control - continuous run & auto start/stop	All models