

Cold Water Gasoline Belt Drive

CWC Premium Series

One of the most powerful cold water pressure washers on the market today, this unit is jobsite ready with 1¼-inch roll cage, handles and lifting hook.



CWC-5004-3MAH
CWC-5004-3MGH
CWC-5005-3MGH

CWC-6004-3MGH



11.5-gallon capacity fuel tank allows for 8-hour running time

Pump

- Belt drive triplex piston AR or General pump with ceramic plungers
- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal and safety relief valves
- Water filter with clear sleeve for screen inspection (High capacity water filter on CWC-3008-3MGH)
- Pump oil drain

Engine

- Performance-proven engine with low-oil protection
- Electric start (battery included)
- Engine oil drain

Frame

- Patented frame design includes powder coated steel frame with 1¼-inch roll cage, handles and lifting hook
- Two-piece belt guard with ¼-turn release for quick access to belts
- Convenient gun/wand holder and hose wrap
- Solid steel threaded axles
- Convenient nozzle holder for quick connect nozzles
- Pneumatic tires with locking tire brake

Components

- Heavy-duty dual cogged belt drive system for increased belt life
- Easy start valve
- Polyethylene fuel tank will not rust

Units Include:

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x ¾-inch non-marking hose with quick connects, swivel and bend restrictors (CWC-5004, CWC-5005 & CWC-6004 models)
- 50-foot x ½-inch hose with quick connects, swivel and bend restrictors on CWC-3008 model
- Professional-grade insulated trigger gun with safety lock-off
- 48-inch lance with rubber grip

Warranties



| MODEL NUMBER | PSI | GPM | DISPLACEMENT/ENGINE | PUMP | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|---------------|------|-----|---------------------|---------|----------------------|----------|---------|
| CWC-3008-3MGH | 3000 | 8.0 | 688cc Honda OHV | General | 43in.x27.75in.x36in. | 511 lb. | 388 lb. |
| CWC-5004-3MAH | 5000 | 4.0 | 688cc Honda OHV | AR | 43in.x27.75in.x36in. | 501 lb. | 378 lb. |
| CWC-5004-3MGH | 5000 | 4.0 | 688cc Honda OHV | General | 43in.x27.75in.x36in. | 501 lb. | 378 lb. |
| CWC-5005-3MGH | 5000 | 5.0 | 688cc Honda OHV | General | 43in.x27.75in.x36in. | 511 lb. | 388 lb. |
| CWC-6004-3MGH | 6000 | 3.7 | 688cc Honda OHV | General | 43in.x27.75in.x36in. | 511 lb. | 388 lb. |

OPTIONS

| PART NUMBER | DESCRIPTION | FITS MODELS |
|--------------|--|----------------------------|
| AW-3000-0035 | Sand injector - Remove coatings from steel and concrete surfaces | CWC-5004 & CWC-6004 models |
| AW-7500-0035 | Rotating nozzle - Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage | CWC-6004-3MGH |