# **Hot Water Natural Gas/LP Belt Drive**

## **HG Series**

Limited Warranties:

1 Year **Electric Motor**  7 Year

Certified for 0 to 2000-feet above sea level

3 Year Coil

### **Pump**

- √ Thermal relief valve
- ✓ Adjustable high pressure detergent injector

✓ Open drip-proof motor with thermal overload protection

#### Frame

✓ Powder coated steel side panels and frame

#### Components

- ✓ Natural gas or LP gas-fired (vapor only) natural draft with aspirating-type burner, 10-inch stack
- ✓ 24-volt control system
- ✓ 1/2-inch schedule 80-coil heat exchanger
- ✓ Electronic ignition with an intermittent pilot

#### **Unit Includes:**

- ✓ 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects
- ✓ Insulated trigger gun with safety lock-off
- ✓ Adjustable pressure insulated dual lance

### Miscellaneous

✓ Maximum outlet temperature is 200°F (250°F/121°C outlet temperature with steam option)



The stationary HG Series is a perfect choice for wash bays that require a steady fuel source. Available in either natural gas or LP, these units feature an electronic ignition with an intermittent pilot.



| MODEL NUMBER | PSI  | GPM | HORSEPOWER/MOTOR        | PUMP    | Mi-T-M<br>NO. | UNLOADER       | BTU PER HR.<br>NATURAL GAS |         | DRAFT<br>DIVERTER | NOZZLES            | DIMENSIONS<br>(LxWxH) | SHIP WT. | NET WT. |
|--------------|------|-----|-------------------------|---------|---------------|----------------|----------------------------|---------|-------------------|--------------------|-----------------------|----------|---------|
| HG-3004-1208 | 3000 | 3.9 | 8.0 HP, 208V, 1Ø, 40.5A | General | 3-0202        | Factory preset | 338,000                    | 326,000 | 21in.             | 0°, 15°, 25° & 40° | 56.5x29x49.75in.      | 878 lb.  | 758 lb. |
| HG-3004-3208 | 3000 | 3.9 | 8.0 HP, 208V, 3Ø, 23.0A | General | 3-0202        | Factory preset | 338,000                    | 326,000 | 21in.             | 0°, 15°, 25° & 40° | 56.5x29x49.75in.      | 878 lb.  | 758 lb. |
| HG-3004-1230 | 3000 | 3.9 | 8.0 HP, 230V, 1Ø, 37.0A | General | 3-0202        | Factory preset | 338,000                    | 326,000 | 21in.             | 0°, 15°, 25° & 40° | 56.5x29x49.75in.      | 878 lb.  | 758 lb. |
| HG-3004-3230 | 3000 | 3.9 | 8.0 HP, 230V, 3Ø, 20.0A | General | 3-0202        | Factory preset | 338,000                    | 326,000 | 21in.             | 0°, 15°, 25° & 40° | 56.5x29x49.75in.      | 878 lb.  | 758 lb. |
| HG-3004-3460 | 3000 | 3.9 | 8.0 HP, 460V, 3Ø, 10.0A | General | 3-0202        | Factory preset | 338,000                    | 326,000 | 21in.             | 0°, 15°, 25° & 40° | 56.5x29x49.75in.      | 878 lb.  | 758 lb. |

| Options:    |   |             |                    |      |   |
|-------------|---|-------------|--------------------|------|---|
| PART NUMBER | DESCRIPTION                                       | FITS MODELS | PART NU            | MBER | MBER DESCRIPTION  |
| HX-0104     | K7 unloader, flow activated (auto start/stop N/A) | All models  | HX-0110            |      | Additional remotes (up to 3)                              |
| HX-0105     | Liquid propane (vapor only)                       | All models  | HX-0111            |      | Auto start/stop   |
| IX-0106     | Hour meter  | All models  | HX-0121            |      | 250°F steam upgrade                                       |
| IX-0107     | Time delay shutdown                               | All models  | HX-0124            |      | Auto start/stop and first remote option                   |
| HX-0108     | (1) remote station (auto start/stop N/A)          | All models  | Note: You cannot o | n    | order HX-0107 and HX-0108 together, you will need to orde |
| HX-0109     | Time delay shutdown and first remote box          | All models  | HX-0107 and HX-0   |      | 108 can be ordered separately.                            |