SUPERMAX DOUBLE DRUM SANDERS 25"/ 37"/50" WIDTHS



EXCEPTIONAL SUPERMAX FEATURES

INTELLISAND Technology: Automatically adjusts conveyor speed based on load

• Prevents gouging, damaging or burning stock

• Provides consistent finish even with varying grain pattern and density

• Greatly increases abrasive planing and dimensioning speed

Flatness Guarantee: Precision-flattened steel conveyor bed reinforced with four steel cross sections for no "flex" in conveyor, guaranteeing flatness to less than .010" across the width of the sander

Abrasive conveyor belt offers the best grip for raw wood, giving you the ability to accommodate stock that is much shorter or thinner

Patented Abrasive Attachment System effectively tensions the abrasive wraps, preventing loose abrasive and overlap

Self-cooling drum prevents overheating and extends abrasive life

Conding Consoitus	
Sanding Capacity:	
Maximum Width (in):	25, 37 or 50
Minimum Length (in):	3-1/2
Maximum Thickness (in):	25" model: 6 37" & 50" models: 12
Minimum Thickness (in):	1/32
Dimensions H x W x D (in):	25" model: 43 x 46 x 31 37" model: 43 x 58 x 31 50" model: 50 x 71 x 31
Drum (in): extruded aluminum	25" model: 5 x 25 37" model: 5 x 37 50" model: 5 x 50
Drum speed:	1740 RPM
Dust Hood: steel, hinged at back	25" model: (2) - 4" ports, min. 1000 CFM recommended 37" & 50" models: (3) - 4" ports, min. 1800 CFM recommended
Ball Bearings (1"):	4 - permanently sealed and lubricated
Conveyor Motor :	25" & 37" models: 100 inlb. torque, direct drive D.C motor, infinitely variable, 0-15 FPM 50" model: 220 inlb. torque, direct drive D.C motor, infinitely variable, 0-15 FPM
Drive Motor (TEFC):	25" & 37" models: 5 HP 50" model: 7-1/2 HP
Power Requirements:	208-230V, 60HZ; 1 PH, 30 amp service; 3 PH, 20 amp service
Shipping Weight (lbs):	25" model: 475 37" model: 525 50" model: 820



ADDITIONAL FEATURES

- Cast stand, zinc-plate steel bed, centerless ground column tubes
- Drums are wrapped with 80 and 120 grit sandpaper
- Swivel & lock casters included on 37" and 50" models
- Electric Height Adjustment and Digital Read Out included on 50" model

Item#	Description
913002	25x2 Double Drum Sander- 220V, 5 HP, Single Phase
913102	25x2 Double Drum Sander- 220V, 5 HP, 3 Phase
937003	37x2 Double Drum Sander- 220V, 5 HP, Single Phase
937103	37x2 Double Drum Sander- 220V, 5 HP, 3 Phase
750102	50x2 Double Drum Sander- 220V, 7-1/2 HP, Single Phase
750302	50x2 Double Drum Sander- 220V, 7-1/2 HP, 3 Phase

25" and 37" models are made in Taiwan to SuperMax specifications. The 50" model is made in the USA.